

全效型濾水器

AP Easy Complete

- 有效過濾可致癌揮發性有機化學物。
Effectively reduce Volatile Organic Chemicals (VOCs).
- 有效過濾鉛、鐵銹、沉積物、氯、異味。
Effectively reduce lead, rust, sediment, chlorine taste and odor.
- 有效過濾99.99%之隱孢子蟲。
Effectively reduce 99.99% cysts.



高效型濾水器

AP Easy LC

- 有效過濾鉛、鐵銹、沉積物、氯、異味。
Effectively reduce lead, rust, sediment, chlorine taste and odor.
- 有效過濾99.99%之隱孢子蟲。
Effectively reduce 99.99% cysts.



過濾效能

Reduction Capability

採用先進多功能合一設計，一支濾芯已具備多項過濾效能。
Adopt advanced multi-function design to fulfill various reduction capability with one cartridge only.

功能 Function				
產品型號 Model	鐵銹及沉積物 Rust and Sediment	氯氣及異味 Chlorine Taste and Odor	鉛及隱孢子蟲 Lead and Cysts	揮發性有機化學物* Volatile Organic Chemicals(VOCs)*
全效型濾水器 AP Easy Complete	✓	✓	✓	✓
高效型濾水器 AP Easy LC	✓	✓	✓	

*包括苯、對二氯苯和毒殺芬
#Include Benzene, P-Dichlorobenzene and Toxaphene

先進多功能合一設計
Advanced Multi-function Design

採用美國FDA (食品及藥物管理局) CFR-21認可物料製造。
Made from FDA CFR-21 (Food Grade) Compliant Materials.

系統由美國製造。
System manufactured in USA.



規格

Specification

產品型號 Model	全效型濾水器 AP Easy Complete	高效型濾水器 AP Easy LC
過濾精密度 Micron Rating	0.5 微米 0.5 micron	0.5 微米 0.5 micron
有效過濾水量 Capacity	750 加侖(2,839 公升) 750 gallons(2,839 liters)	750 加侖(2,839 公升) 750 gallons(2,839 liters)
流量 Flow Rate	0.75 加侖/分鐘(2.84 公升/分鐘) 0.75 gpm (2.84 lpm)	0.75 加侖/分鐘(2.84 公升/分鐘) 0.75 gpm (2.84 lpm)
適用水溫 Operating Temperature	4.4 °C - 37.8 °C	4.4 °C - 37.8 °C
適用水壓 Operating Pressure	25 - 120 psi	25 - 120 psi
尺寸 Dimension	32cm(H) x 7.4cm(W) x 6.9cm(D)	27cm(H) x 7.4cm(W) x 6.9cm(D)
濾芯 Cartridge	全效型濾芯 AP Easy C-Complete	高效型濾芯 AP Easy C-LC

使用須知:

1. 當水流速度減慢時應更換濾芯，建議每6至9個月更換濾芯一次，但亦視乎用水量及水質而異，濾芯最長使用期為12個月。
2. 如水源懷疑受污染或未經任何消毒處理，請勿使用本產品。
3. 安裝及使用本產品前，請先閱讀安裝及操作指引以避免因漏水而引致任何財物損失。
4. 只適用於家居冷水處理。
5. 本公司並不承擔因保養失當而造成之產品故障。

Instructions:

1. Change the cartridge when the water flow becomes slow. Suggest to change cartridge every 6-9 months. Maximum cartridge life is 12 months but varies by water consumption and water quality.
2. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection.
3. To avoid property damage due to water leakage, you must read the installation and operating manual before installing and using this product.
4. For residential use only with cold water.
5. 3M will not be liable for system failure due to improper maintenance.

榮獲美國國家衛生基金會認證



NSF/ANSI Std. 53
健康效應

NSF/ANSI Std. 42
感觀效應

